



What about TIS Measurements in 3 min/channel?

Fast TIS Option for HP700

Fast TIS Option for HP700 delivers TIS results in 3 minutes per channel

The Bluetest newly developed algorithm for TIS measurements together with the Bluetest chamber technology enables the TIS measurements in only 3 minutes/channel. Together with the markets fastest TRP measurements, the Fast TIS option will dramatically increase the throughput in the test lab.

Improve your Test Throughput

The easy handling of the HP700 chamber and the MIMO/LTE option makes the testing faster and more effective than with other solutions on the market. HP700 is designed with usability in mind, which means that the down time of the chamber due to maintenance is reduced to a minimum. The calibration is extremely simple and can be performed by the operator in less than 15 minutes.

Best in Class Accuracy, Repeatability and Stability

Accuracy of the measurements in the HP700 is very good and measurements can be repeated again and again with the same result. The robust design of the software and hardware makes the stability something that users don't need to worry about.

Future Proof Investment

Due to the realistic multi-path test method used in HP700 it is easily extended to any future technologies. The design is scalable, which means that an investment only needs to contain the technology that is used in the development right now. Technologies that will be used tomorrow can be added tomorrow. Small foot print means that the chamber easily can be placed at any location in the lab or office and is easily movable to a new place if required.

Specification Fast TIS Option

Supported Technologies

GSM
WCDMA

Test Time

Typical 3 minutes/channel

Base Station Simulator

Agilent 8960
Anritsu MT8815/8820

Order Number

GSM:
Agilent 8960 256-1
Anritsu MT8815/8820 256-2

WCDMA:
Agilent 8960 257-1
Anritsu MT8815/8820 257-2

Bluetest AB

Götaverksgatan 1, SE-417 55 Göteborg
SWEDEN,
sales@bluetest.se, +46 733 24 48 58

Product specification and descriptions in this document are subject to change without notice.



General Specification HP700

General Specification

Frequency Range: 650 – 6000 MHz
Accuracy TRP: 0.5 dB (STD)
Accuracy TIS: 0.7 dB (STD)
Repeatability: 0.2 dB (STD)
Test Time TRP (typical): 1 min/channel
Test Time TIS (typical): 10 min/channel
Test Time TIS (Fast TIS option): 3 min/channel*
*GSM and WCDMA

Dimensions

Length: 2000 mm
Height: 2000 mm
Depth: 1400 mm

Supported Technologies

TRP/TIS Measurements: GSM
GPRS/EDGE
WCDMA
HSPA
CDMA2000
EVDO Rev 0 and A
LTE
Bluetooth
WLAN 802.11b/g

Throughput Measurements: LTE
WLAN

Supported Base Station Simulators

Agilent 8960/N4010A
Anritsu MT8815/8820/8860
Rohde & Schwarz CMU 200/CMW 500

World Wide Sales

AUSTRIA, GERMANY and SWITZERLAND

GIGACOMP
Bernd Fleischmann, bernd.fleischmann@gigacomp.de, Tel. +49 89 3220 8957

FINLAND

Weltest Systems Ky
Vesa Kauppinen, vesa.kauppinen@weltestsystems.com, Tel: +35 8500 553 009

UK and ITALY

MI Technologies Carlo Rizzo, crizzo@mi-technologies.eu,
Tel. +44 8700 555 010

USA, CANADA and MEXICO

MI Technologies Kirk Anderson, kanderson@mi-technologies.com, Tel: +1 678 475 8378

JAPAN

TOYO Corporation Shogo Etoh, etoh@toyo.co.jp, Tel. +81 3 3279 0771

KOREA

Dymstec Kyung-soon Choi, angela@dymstec.com Tel. 82-31-777-8455

TAIWAN

QuieTek Corporation
David Cheng, davidcheng@quietek.com, Tel. +886 2 8601 3638

CHINA

Corad Technology Limited
Ken Guan, hj.guan@tnmcorad.com, Tel +86 21 6466 9185
QuieTek Corporation
David Cheng, davidcheng@quietek.com, Tel. +886 2 8601 3638

ST Electronics

Simon Yip Weng Peng, simonyip@stee.stengg.com, Tel: +65 6568 6346

ASEAN

ST Electronics Simon Yip Weng Peng, simonyip@stee.stengg.com, Tel: +65 6568 6346,